

1° Pos.	2° Pos.	3° Pos.	4° Pos.	5° Pos.	6° Pos.	7° Pos.	8° Pos.
7	8	F	D	4	A	1	Z

9° Pos.	10° Pos.	11° Pos.	12° Pos.
7	8	M	A

TYPE:	
78	7/8" CONNECTOR

CONNECTOR TYPE:	
M	MALE CONNECTOR
F	FEMALE CONNECTOR
Y	MALE INTERNAL-CORE WITH 7/8" FEMALE THREAD
Z	FEMALE INTERNAL-CORE WITH 7/8" MALE THREAD

MODEL:	
A	ANGLED 90° WITH MOULDED CABLE
D	STRAIGHT 180° WITH MOULDED CABLE
C	FIELD ATTACHABLE 180°
P	PANEL FRONT MOUNTING WITH SOLDER CONTACTS.
R	PANEL BACK MOUNTING WITH SOLDER CONTACTS.
Q	PANEL FRONT MOUNTING WITH PCB CONTACTS.
S	PANEL BACK MOUNTING WITH PCB CONTACTS.

1° POSITION = METERS		2° POSITION (LETTER)=DECIMETRES	
1	1 METER	Z	0
2	2 METERS	A	10 CENTIMETERS
3	3 METERS	B	20 CENTIMETERS
4	4 METERS	C	30 CENTIMETERS
	... ETC.	D	40 CENTIMETERS
		E	50 CENTIMETERS
			... ETC.
		2° POSITION (NUMBER)=BESIDES 10 M	
		0	10 METERS
		5	5 METERS

POLES NUMBER	
3	3 POLES
4	4 POLES
5	5 POLES
6	6 POLES

EXTENSION		
11° POSITION		12° POSITION
M	MALE CONNECTOR	SEE MODEL SCHEME
F	FEMALE CONNECTOR	
Y	MALE INTERNAL-CORE WITH 7/8" FEMALE THREAD	
Z	FEMALE INTERNAL-CORE WITH 7/8" MALE THREAD	

CABLE CODIFICATION	
A	PVC/PVC 1,50 BLACK
B	PVC/PVC 2,50 BLACK
C	PUR/PP 1,50 BLACK
D	PUR/PP 2,50 BLACK
E	PVC/PVC 1,50 BLACK UL/CSA
F	PVC/PVC 2,50 BLACK UL/CSA
G	PVC/PVC 1,5 GREY
6	PVC/PVC 0,75 BLACK SHIELDED
8	PVC/PVC 1,5 GREY SHIELDED
9	PVC/PVC 2,5 GREY SHIELDED

—

—